



Designation: D5760 – 19

Standard Specification for Performance of Manual Transmission Gear Lubricants¹

This standard is issued under the fixed designation D5760; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (^ε) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification lists the test methods and acceptance criteria for determining the acceptability of lubricants used in nonsynchronized heavy duty manual transmissions.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.3 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:²

- D130 Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test
- D892 Test Method for Foaming Characteristics of Lubricating Oils
- D5182 Test Method for Evaluating the Scuffing Load Capacity of Oils (FZG Visual Method)
- D5579 Test Method for Evaluating the Thermal Stability of Manual Transmission Lubricants in a Cyclic Durability Test
- D5662 Test Method for Determining Automotive Gear Oil Compatibility with Typical Oil Seal Elastomers
- D5704 Test Method for Evaluation of the Thermal and Oxidative Stability of Lubricating Oils Used for Manual Transmissions and Final Drive Axles
- D7603 Test Method for Determination of Storage Stability and Compatibility in Automotive Gear Oils

¹ This specification is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.B0.03 on Automotive Gear Lubricants & Fluids.

Current edition approved May 1, 2019. Published June 2019. Originally approved in 1995. Last previous edition approved in 2013 as D5760 – 13. DOI: 10.1520/D5760-19.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

2.2 SAE Publications:³

SAE J2360 Lubricating Oil, Gear Multipurpose (Metric) Military Use

3. Terminology

3.1 Definitions of Terms Specific to This Standard:

3.1.1 *nonsynchronized transmission, n*—a transmission having no means for synchronizing the speeds of engaging elements. Typical heavy-duty manual transmissions have no such means for gear engagement by the shift lever, but may have such means for pneumatic engagement of auxiliary range gears.

3.1.2 *oil seal compatibility, n*—in lubricants for lubricating manual transmissions and final drive axles, prevention of chemical or thermal degradation of seal elastomers typically observed as hardening, cracking, or excessive swelling in a manner which would result in oil leakage.

3.1.3 *thermal oxidation, n*—in lubricants used for lubricating manual transmissions and final drive axles, deterioration of the lubricant under high-temperature conditions which is observed as viscosity increase of the lubricant, insolubles formation in the lubricant, deposit formation on the parts, or a combination thereof.

4. Performance Classification

4.1 *API Category MT-1*—The designation API Category MT-1 identifies the category of lubricants intended for use in nonsynchronized manual transmissions, apart from API Service Category GL-4. See [Appendix X1](#) for background information on this category.

5. Performance Requirements

5.1 API Category MT-1 performance requirements for candidate gear lubricants are provided in [Table 1](#).

6. Number of Tests and Retests

6.1 *Test Method D5704*—In determining whether an oil meets the required limits the following rules shall apply:

6.1.1 No more than three operationally valid tests are to be conducted for compliance testing.

³ Available from SAE International (SAE), 400 Commonwealth Dr., Warrendale, PA 15096-0001, <http://www.sae.org>.

*A Summary of Changes section appears at the end of this standard

**TABLE 1 API Category MT-1 Category Tests and Acceptance Criteria**

Test Item	Minimum	Maximum
Test Method D5704		
Viscosity increase, %	...	100 %
Pentane insolubles, %	...	3.0 %
Toluene insolubles, %	...	2.0 %
Carbon/varnish rating	7.5	...
Sludge rating	9.4	...
Test Method D5662		
Polyacrylate @ 150 °C, 240 h		
Elongation change, %	-60	+no limit
Hardness change, points	-35	+5
Volume change, %	-5	+30
Fluoroelastomer @ 150 °C, 240 h		
Elongation change, %	-75	+no limit
Hardness change, points	-5	+10
Volume change, %	-5	+15
Test Method D5579	better than passing reference oil ^A	...
Test Method D130 ^B	...	2a
Test Method D5182		
Failing load stage	11	...
Test Method D892, foam tendency only		
Sequence I, mL	...	20
Sequence II, mL	...	50
Sequence III, mL	...	20
Test Method D7603 ^C	pass	...

^A This is defined by the mean of the last five passing reference oil test results used to calibrate the test stand.

^B Tested for 3 h at 121 °C.

^C Shall pass the performance requirements as specified in SAE J2360.

6.1.2 L-60-1 data used for API Category MT-1 approval cannot be generated prior to ASTM Test Monitoring Center (TMC)⁴ calibration of the stand for all API Category MT-1

⁴ ASTM Test Monitoring Center (TMC), Carnegie Mellon University, 6555 Penn Avenue, Pittsburgh, PA 15206, <http://astmtmc.cmu.edu>.

parameters. Stand bias adjustment factors based on reference oil test results are applied when appropriate.

6.1.3 After applying any appropriate stand bias adjustment factors, the first test shall meet or exceed all limits.

6.1.4 After two tests, the average of the two results on all parameters shall meet or exceed the limits.

6.1.5 After three tests, one test is excluded in its entirety. The average of the two results on all parameters shall meet or exceed the limits.

6.2 Test Method D5662—This test method includes testing on two different elastomer materials. No rules regarding multiple testing have been defined.

6.3 Test Method D5579:

6.3.1 No more than four operationally valid tests are to be conducted for compliance testing.

6.3.2 The four allowed tests can be conducted on any combination of test stands approved and referenced by the ASTM Test Monitoring Center (TMC).⁴

6.3.3 If two test results are obtained, each of which is equal to or less than the mean minus the pooled standard deviation for all calibrated test stands in the industry, the fluid is disqualified. The pooled standard deviation is available from the ASTM Test Monitoring Center (TMC).⁴

6.3.4 A test result that meets or exceeds the mean of the last five passing reference oil test results used to calibrate the test stand is considered a pass.

7. Keywords

7.1 API Category MT-1; cyclic durability; manual transmissions; oil seal; thermal oxidation; thermal stability

APPENDIX

(Nonmandatory Information)

X1. API CATEGORY MT-1 RATIONALE

X1.1 In 1986, Eaton Corporation, through the Society for Automotive Engineers (SAE), outlined the trucking industry's need for a gear lubricant category that would provide performance characteristics essential to ensure optimum service life for heavy-duty manual transmissions. This request was supported by all major North American commercial transmission builders.

X1.2 During the same period user surveys indicated that the class of oils typically used in manual transmissions was not always in compliance with the builder's primary recommendations. API GL-5 gear oils or multigrade engine oils were the popular choice of users due to their desire to inventory and use two shop oils, engine and gear. Some of these oils were found to perform satisfactorily while others presented problems. In extreme cases, some API GL-5 oils were reported to cause oil seal failures due to coking/hard deposits or severe oil sludging

at mileages below realistic drain intervals, or both.

X1.3 Using feedback from equipment builders, SAE outlined several lubricant performance characteristics that they believed were vital to ensure that their goals for optimum transmission service life would be met. These characteristics included the following:

- (1) Fluid thermal stability/component cleanliness,
- (2) Oil seal compatibility, and
- (3) Brass (copper) component compatibility.

X1.4 ASTM was then requested to identify or develop tests suitable to assess the preceding performance characteristics. In the process, the proposed category's performance test matrix was expanded to include properties in addition to those originally defined in order to ensure that a performance balanced lubricant would be provided to users. The added



properties included antiwear, foam control, and lubricant compatibility. A full-scale transmission test was also included to reaffirm the high-temperature lubricant performance capabilities of API Category MT-1. This test correlates with field service and also ensures satisfactory performance with plate-type synchronizers.

X1.5 The tests and acceptance criteria defined by this specification are the result of specification and test method development work within ASTM. The introduction of this new

category will allow OEMs to specify gear oils for manual transmissions that can be made available either as dedicated fluids (API Category MT-1) or multipurpose fluids (that is, API GL-5/API Category MT-1). Oils meeting the API Category MT-1 performance definition will satisfy OEM objectives for optimum transmission performance and service life. This has been achieved by combining in a single lubricant the cleanliness and oil seal life typical of engine oils with the load carrying characteristics of gear oils.

SUMMARY OF CHANGES

Subcommittee D02.B0.03 has identified the location of selected changes to this standard since the last issue (D5760 – 13) that may impact the use of this standard. (Approved May 1, 2019.)

(1) Added Test Method **D7603** to Referenced Documents; removed Federal Specifications from Referenced Documents.

(2) Revised **Table 1**.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; <http://www.copyright.com/>